



Machine colour:
RAL 9006 = white-aluminium, bright
RAL 4008 = signal violet

Ambient: +5°C ... +45°C
Relative humidity: max. 85%

min floor loading: 1500 kg/m²

WP = Welding point

	A	B	C	D	Material:	Oberfläche:	Bemerkung:	
CM16-S	Electrical Supply	Water inlet	Water outlet	Air Supply	Dimension:	Masse in kg:	Technical changes reserved !	
	3x400 VAC+N+Ground Power: 35 kVA Control voltage: 24 VDC Fuse: 3 x 32 A	Connection G 1/2" Pressure 5 ... 6 bar Pump capacity min 20 l/min Cooling power min 10 kW	Connection G 3/4" Backpressure max 1 bar	Connection: G 1/2" Pressure min: 5 bar Consumption: 5...20 m ³ /h	CM 16 - SILENTIUM Layout	kg	Schutzvermerk nach DIN 34 beachten.	
Chiller	Electrical Supply	Water inlet	Water outlet	Air Consumption 5640 m ³ /h			Bezeichnung:	Masse in kg:
	3x400 VAC+N+Ground Power: 4.5 kW Cooling power 10.5 kW	Connection Water preliminary heat 5...25° Environment temp. 10...43°	Connection G 3/4" Pressure 6 bar Pump capacity min 25 l/min		CM 16 - SILENTIUM Layout	kg	Geprüft ER 30.04.2018	
					Format: A3		Blatt: 1 / 1	zuletzt gespeichert am: Montag, 30. April 2018 11:14:15
CAN MAN							16_00_00001	-