



Machine colour:
RAL 9006 = white-aluminium, bright
RAL 4008 = signal violet

Ambient: +5°C ... +45°C
Relative humidity: max. 85%

min floor loading: 1500 kg/m²

WP = Welding point

	A	B	C	D	Material:	Oberfläche:	Bemerkung:
	Electrical Supply	Water inlet	Water outlet	Air Supply	Dimension:	Masse in kg:	Technical changes reserved !
X4	3x400 VAC+N+Ground Power: 50 kVA Control voltage: 24 VDC Fuse: 3 x 125 A	Connection G 3/4" Pressure 5 ... 6 bar Pump capacity min 40 l/min Cooling power min 15 kW	Connection G 1/1" Backpressure max 1 bar	Connection: G 3/4" Pressure min: 6 bar Consumption: 25 m ³ /h	Bezeichnung: X4 WeldCENTER™ Layout	kg	Schutzvermerk nach DIN 34 beachten.
Chiller	Electrical Supply 3x400 VAC+N+Ground Power: 15.5 kW Cooling power 30 kW	Water inlet Connection Water preliminary heat 5...25° Environment temp. 10...43°	Water outlet Connection G 3/4" Pressure 5.6 bar Pump capacity 60 l/min	Air Consumption 9'900 m ³ /h			Masstab Gezeichnet PB 20.03.2013 1:40 Geprüft ER 24.04.2018 Filemaker-Nr 016000
						Format: A3	Blatt: 1 / 1 zuletzt gespeichert am: Dienstag, 24. April 2018 15:45:28
					CAN MAN		14_00_00001 -