



Machine colour:
RAL 9006 = white-aluminium, bright
RAL 4008 = signal violet

Ambient: +5°C ... +45°C
Relative humidity: max. 85%

min floor loading: 1500 kg/m²

	A	B	C	D	Material:	Oberfläche:	Bemerkung:
	Electrical Supply	Water inlet	Water outlet	Air Supply	Dimension:	Masse in kg:	Technical changes reserved !
X5	3x400 VAC+N+Ground Power: 35 kVA Control voltage: 24 VDC Fuse: 3 x 32 A	Connection G 1/2" Pressure 5 ... 6 bar Pump capacity min 25 l/min Cooling power min 10 kW	Connection G 3/4" Backpressure max 1 bar	Connection: G 1/2" Air pressure min: 5 bar Air consumption: 42 m ³ /h	Bezeichnung: X5 WeldCENTER™ Layout		Schutzvermerk nach DIN 34 beachten.
Chiller	Electrical Supply	Water inlet	Water outlet	Air consumption: max. 8'250 m ³ /h	Format: A3		Masstab Gezeichnet mwi 04.09.2015 1:35 Geprüft MB 26.03.2021 Filemaker-Nr 009909
	3x400 VAC+N+Ground Power: 4.5 kW Cooling power 10.5 kW	Temperature 5...25° Environment temp. 10...43°	Connection G 1/2" Pressure 6 bar Pump capacity min 25 l/min		Blatt: 1 / 1		zuletzt gespeichert am: Freitag, 26. März 2021 17:06:03
CAN MAN							15_00_00000