



	A Electrical Supply	B Water inlet	C Water outlet	D Air Supply	Material:	Oberfläche:	Bemerkung:
					Dimension:	Masse in kg:	Technical changes reserved !
X8	3x400 VAC+N+Ground Power: 15 kVA Control voltage: 24 VDC Fuse: 3 x 32 A	Connection G 1/2" Pressure min 6 bar	Connection G 3/4" Backpressure max 1 bar	Connection: G 1/2" Air Pressure min: 5 bar Air Consumption: 42 m ³ /h	Bezeichnung: X8 WeldCENTER™		Schutzvermerk nach DIN 34 beachten.
Chiller	3x400VAC+Ground,50/60Hz Power: 5.3 kW 3x460VAC+Ground,50/60Hz Power: 11.3 kW	Volume min 35 l/min Set temp. min 15°C Environment temp. 10...43° Cooling power min. 10 kW		Air Consumption: max. 8'250 m ³ /h	Layout		Masstab Gezeichnet MB 29.01.2020 1:25 Geprüft MB 24.03.2021 Filemaker-Nr 025000
						Format: A3	Blatt: 1 / 1 zuletzt gespeichert am: Mittwoch, 24. März 2021 16:49:55
					CAN MAN		18_00_40000 -